

ImagePro 8101H

Ultra Short Throw LCD Projector



The ImagePro 8101H features a short throw distance to allow placement where user shadow does not affect image viewing

FEATURES

- 2500 Lumens Brightness
- XGA Resolution
- Large filter with side access
- Ultra short 4 to 31 inch throw
- Monitor Loophthrough
- Built-in Anti-theft security
- Dynamic room-filling sound from 7-watt speaker
- No shadow/No glare
- Hybrid 2000 hour filter



THE ALL NEW
DUKANE
Education. Presentation. Inspiration.

www.dukcorp.com/av

ImagePro is a registered trademark of Dukane Corporation
#09081.1

Specifications

Image Element	0.63" polysilicon active-matrix TFT x3
Brightness	2500 ANSI lumens (2000 lumens in Whisper Mode)
Resolution	1024 x 768 pixels (H X V), XGA
Contrast	500:1
Scanning Frequency	fh 15 -106 kHz, fv 50-120 Hz
Lens	Fixed
Lens Throw Ratio	SEE TABLE THIS PAGE
Keystone Correction	Digital, vertical +/-5 deg
Aspect Ratio	4:3, 16:9 selectable
Computer	SVGA, VGA, XGA, SXGA, UXGA
Compatibility	MAC13" and MAC16"
Video Compatibility	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, HDTV (1080i, 720p, 576i, 480i/p)
Image Control	Freeze function, electronic magnification and pan
Closed Caption	CC1, CC2, CC3, CC4, TI, T2, T3, T4
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	220W UHB
Lamp Life	2000 hours (typical) 3000 hours (whisper mode)
Audio	1 speaker 7 watt
Throw Distance	4" to 31"
Screen Size, diagonal	60" to 150"
Inputs, Video	(1) Component, RCA x 3 (1) S-video, Mini DIN 4-pin (1) Composite video, RCA x 1
Inputs, Computer	(2) RGB, 15 pin D-sub
Inputs, Audio	(2) Stereo mini jack: for PC/Access. (1) RCA x 2 (for video)
Outputs, Audio	(1) Stereo mini jack, adjustable
Outputs, Monitor	RGB, 15 pin D-sub
Outputs, Control	RS-232, 9 pin D-sub
Security	Kensington lock slot & Security Bar
Fan Level	33dB, ultra quiet; 28dB Whisper Mode
Operating Temperature	41-95 deg F
Power	AC 100-120V, AC 220-240V 50/60 Hz, 340 watt
Size (WxHxD)	15.6" x 5.2" x 14.0"
Weight	12.8 lbs.
CARTON (WxHxD)	22" X 9.5" X 19"
Shipping Weight	24 lbs.
Accessories Included	Remote control, batteries, power cord, RGB cable, RCA video cable and operators manual.
Safety	UL/C-UL, FCC Class B
Optional Accessories	Lamp 456-8101H Wall; 8100WALLARM Ceiling Mount, Universal; RPM-U Filter; UX35381

Five (5) year limited warranty on parts and labor in North America, lamp excluded
(for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-
Mind Loaner Program.

5YR